

Specially designed for testing pressurized equipment

- Readable large display
- Accurate and easy-to-use
- Robust ABS casing
- Time-stamped monitoring
- Differential measurements
- Auto-Stop



Measurement range	0 to 6.89 bar
Maximum pressure	10.33 bar
Resolution	0.004 bar
Accuracy	0.3 % full scale
Response time	0.5 s
Unit selection	psi, bar, mbar, inH ₂ O, mm H ₂ O, mm Hg, OZin ² , kg/cm ² , Kpa, Ft H ₂ O, in Hg, cm H ₂ O

Operating conditions:

- Temperature: 0 to 50 °C
- Maximum humidity: 80 % RH

Storing conditions:

- Temperature: -20 °C to +60 °C
- Maximum humidity: 80 % RH

Power supply: 1 x 9 V battery

Dimensions: 72 x 182 x 30 mm

Mass: 220 g (battery included)



Supplied with hard case
and accessories

To order	
C.A 850 Manometer	P01.1841.01

FRANCE
Chauvin Arnoux
190, rue Championnet
75876 PARIS Cedex 18
Tel: +33 1 44 85 44 86
Fax: +33 1 46 27 95 59
export@chauvin-arnoux.fr
www.chauvin-arnoux.fr

UNITED KINGDOM
Chauvin Arnoux Ltd
Waldeck House, Waldeck Road
MAIDENHEAD SL6 8BR
Tel: +44 1628 788 888
Fax: +44 1628 628 099
info@chauvin-arnoux.co.uk
www.chauvin-arnoux.co.uk

LEBANON
Chauvin Arnoux Middle-East
P.O. BOX 60-154
1241 2020 JAL EL DIB (BEIRUT)
Tel: +961 1 890 425
Fax: +961 1 890 424
camie@chauvin-arnoux.com
www.chauvin-arnoux.com

C.A 850

Digital Manometer

Pressure



Production



Electrical,
Mechanical
Maintenance