



FLIR MR77 pinless moisture meter

The FLIR MR77 moisture meter performs all the critical and advanced measurements professionals demand. Rugged design with field replaceable sensors are engineered to reduce downtime.

- Field replaceable temperature and relative humidity sensor
- Integrated IR thermometer provides fast non-contact surface temperature measurements
- Remote pin-type probe (included) allows for contact moisture readings
- Large LCD screen clearly displays moisture, humidity, and air temperature levels
- FLIR Tools Mobile connects the FLIR MR77 to your compatible smartphone and tablet via Bluetooth*
- METERLiNK® technology wirelessly integrates moisture readings on your image with METERLiNK-enabled FLIR Thermal Cameras
- All the sensors you need: Integrated pinless moisture sensor, temperature and relative humidity, IR thermometer and external moisture pin probe

Features:

Grains per pound or grains per kilogram, dew point, condensation point, differential temperature (IR and dew point), material/wood groups, high/low humidity & moisture alarms, store, recall, min/max, data hold, auto power off, bright white LED backlight, low battery indication

Includes:

9V battery, user manual/CD, temperature/RH sensor, wired pin probe and limited lifetime warranty



TECHNICAL SUMMARY	RANGE	BASIC ACCURACY
Pinless moisture	0 to 99.9	Relative
Pinless moisture depth max	0.75in (19mm)	
Pin moisture	0 to 99%WME	
Relative humidity	0 to 99%RH	±2.5%RH
Sensor temperature	-18 to 170°F, -28 to 77°C	±3.6°F, 2°C
IR temperature	-4 to 392°F, -20 to 200°C	±3.5%
IR distance to spot ratio	8 inches away : 1 inch spot size	
IR emissivity	0.95 (fixed)	
Vapor pressure	0 to 20.0kPa	±2%

GENERAL INFORMATION	
Warranty	Limited lifetime*
Bluetooth range max	32ft (10m)

Ordering Information

MR77 Pinless moisture meter
 MR77-NIST ... MR77 with certificate of traceability to NIST
 MR01 Replaceable temp/RH sensor
 MR02 Replacement pin moisture probe

* See www.flir.com for latest compatibility information and more warranty details



FLIR Systems France
 20, bd de Beaubourg
 77183 Croissy-Beaubourg
 France
 Tel. : +33 (0)1 60 37 55 02
 E-mail : flir@flir.com

Distributed by:



testoon.COM
 The measurement website

99, rue Beranger 92320 Chatillon - France
 Tel : +33 (0)1 71 16 17 00; Fax : +33 (0)1 71 16 17 03
www.testoon.com