

Product Data Sheet

Leica RGR 200

Features



- Increase range of Line Laser to 80 m
- Works with L2, L2G, L2P5, L2P5G, L6R, L6G, L4P1
- Large detecting area
- Supports red as well as green laser models
- Acoustic feedback
- Two illuminated displays to allow reading from backside

Technical data

	RGR 200
Working range*	2 m – 80 m (6.6 ft – 262 ft)
Accuracy (switchable)	± 1.0 mm (± 0.04 in) / ± 3.0 mm (± 0.12 in)
Detection window	85 mm (3.3 in)
Detection angle	130°
Detectable spectrum	635 ± 5 nm (red) / 525 ± 5 nm (green) class 2 acc. IEC 60825-1
Illuminated display	front side and back side
Acoustical signal	100 dB / 80 dB / 0 dB
Protection class	IP65 (IEC 60529) dust and jet water
Drop resistance	1.2 m (3.9 ft)
Battery type/life	2 x AA 1.5 V / 40+ hours
Low power alert	digital display
Dimensions (L x W x H)	158 x 73 x 26 mm (6.22 x 2.87 x 1.02 in)
Weight with batteries	250 g (0.55 lbs)
Automatic shut-off	30 min without detection
Operating temperature	-10... +50 °C (+14... +122 °F)
Storage temperature	-25... +70 °C (-13... +158 °F)

* Depending on lighting conditions

Scope of Delivery



Leica RGR 200
Art. No. 866090

Leica RGR 200, clamp for staff, 2 x AA batteries

Extended Warranty



Register your product within 8 weeks of purchase at www.disto.com/warranty and benefit from our 3-year warranty.

Distributed by:

testoon.COM
The measurement website



99 rue Beranger 92320 Chatillon - France

Tel. : +33 (0) 1 71 16 17 00

E-mail: contact@testoon.com

www.testoon.com

Dealer Stamp



in accordance with IEC 60825-1

Illustrations, descriptions and technical specifications are subject to change without prior notice. (V 1.0)
Copyright© Leica Geosystems AG, Heerbrugg, Switzerland, 2022.

Leica Geosystems AG
Heerbrugg, Switzerland
www.leica-geosystems.com

- when it has to be **right**

Leica
Geosystems