

Sefram

SEFRAM 7357

Process Multimeter 50.000 counts TRMS AC+DC, high accuracy

Capabilities

Multimeter

- Measure voltages up to 1000V TRMS AC+DC and 1000V DC
- Basic accuracy : 0,05%
- Measure currents up to 1A
- Frequency counter
- Measure resistance up to 50 Mohms
- Continuity test with buzzer
- Diode test
- Digital filter for high accuracy and stability

Process calibrator

- Current source 4-20mA or 0-20mA
- Step mode with pre-defined values or user defined
- Automatic or manual ranges
- Simulator mode with % and Delta %
- Loop power mode (24V/24mA) and HART mode

General capabilities

- Memory : 1000 measures
- Functions : MIN/MAX/AVG, REL, HOLD, Auto HOLD
- Opto isolated USB interface
- PC software WINDMM507 (supplied)
- Safety: 600V CAT IV and 1000V CAT III

Unique ergonomy with navigator

The SEFRAM 7357 process multimeter uses a unique navigator to access and navigate in the menus and functions provided. All basic functions (V, A Ω , ...) are kept with direct access for time saving.

Process functions

The SEFRAM 7357 offers not only a current source (4-20mA or 0-20mA),but can work in simulate mode in your process loop. Current ramps can be generated automatically with standard parameters or user defined parameters. The SEFRAM 7357 can be used as a loop power and can supply sensors, measuring the sourced current. In HARTmode, a 250 ohms resistor is inserted in the loop in order to communicate with HART sensors or intelligent instruments.



TRMS
AC+DC

4-20mA
and
0-20mA

Loop
power

600V CAT IV
1000V CAT III

SEFRAM 7357

Hi-accuracy and TRMS AC+DC measurements

The Process DMM SEFRAM 7357 provides a basic accuracy of 0,05% in V DC. In AC mode, TRMS AC and TRMS AC+DC mode permit measurements on complex signals with large bandwidth (10kHz).





SEFRAM 7357

Process Multimeter 50.000 counts

Specifications		Sefram 7357
Multimeter		7357
DC voltages		
Ranges		50mV to 1000V in 6 ranges
Basic accuracy		$\pm(0,05\% + 5\text{dgt})$
Resolution		1 μ V to 0,1V
AC voltages (TRMS AC et TRMS AC+DC)		
Ranges		50mV to 1000V in 6 ranges
Resolution		1 μ V to 0,01V
Basic accuracy (AC)		$\pm(0,5\% + 20\text{dgt})$ from 5% to 100% of the range
Basic accuracy in AC, AC+DC		$\pm(1,55\% + 25\text{dgt})$ from 5% to 100% of the range
Bandwidth		40Hz to 10kHz (according to range)
DC currents		
Ranges		50mA and 1A
Basic accuracy		$\pm(0,05\% + 5\text{dgt})$
Resolution		from 1 μ A to 50mA
Protection		with HBC fuse 0.44A / 1000V
AC current (TRMS AC et TRMS AC+DC)		
Ranges		50mA and 1A
Resolution		from 1 μ A to 50mA
Basic accuracy		$\pm(1,0\% + 20\text{dgt})$ from 5% to 100% of the range
Bandwidth		40Hz to 10kHz
Protection		with HBC fuse 0.44A / 1000V
Frequency (AC currents and voltages)		
Ranges		500Hz to 100kHz (10kHz for AC currents)
Basic accuracy		$\pm(3\text{dgt})$
Sensitivity		1V p-p from 5Hz to 100kHz and 10mA/300mA in current from 5Hz to 10kHz
Protection		same as current or voltage ranges
Resistance		
Ranges		500ohms to 50Mohms in 6 ranges
Basic accuracy		$\pm(0,2\% + 10\text{dgt})$
Protection		1000Vrms or DC
Continuity test		yes, with buzzer (threshold 30 ohms), $\pm(0,1\% + 30\text{dgt})$
Diode test		yes, with 1mA test current
Accuracy		$\pm(1\% + 20\text{dgt})$
Functions		MIN, MAX, AVG (average), REL, HOLD, Auto Hold
Process calibrator		
Current source mode		
Ranges		0 to 20mA or 4mA to 20mA (overrange possible up to 24mA)
Basic accuracy		$\pm(0,05\% + 5\text{dgt})$
Resolution		1 μ A
Protection		with HBC fuse 0.44A / 1000V
Rampe de courant (mode source)		
Ramps		"linear, 0% to 100% and back to 0% in 40s linear, 0% to 100% and back to 0% in 20s 25% steps, 0 to 100%, 15s for each step 25% steps, 0 to 100%, 5s for each step" same as current accuracy and protection
Basic accuracy, protection		same as source mode, but DMM uses external power supply (6 to 48V)
Current ramp (simulator mode)		
Loop supply		
Ranges		current: 50mA / voltage: 30V / Impedance: 1,25k Ω
Accuracy		$\pm(0,05\% + 5\text{dgt})$
Protection		with HBC fuse 0.44A / 1000V
Loop supply - 250 HART mode		
Ranges		current: 50mA / voltage: 24V / Impedance: 1k Ω
Accuracy		$\pm(0,05\% + 5\text{dgt})$
Protection		with HBC fuse 0.44A / 1000V
General specifications		
Display type		LCD, with automatic backlight
Display counts		5 digits, 50.000 counts
Measurement rate		10 measures/s
Memory		100 measures
Operating temperature		-10°C to 50°C
Storage temperature		-20°C to 60°C (without batteries), RH < 80%
Protection		electronic, except current ranges protected with HBC fuse
Power supply		4 x 1.5V - LR6 AA batteries / Autonomy: 120h typical with alkaline batteries / 10h typical in current source mode after 20mn approx. Or disabled
Auto Power-off		95 x 52 x 207mm
Dimensions		630g, with holster
Weight		600V CAT IV and 1000V CAT III
Safety		1 year
Warranty		

Supplied with : a set of safety test leads, user manual, opto-isolated USB cable, WINDMM507 software for PC, batteries (installed).



FT7357 A 00- Specifications can be updated without notice.



Distributed by:



testoon.COM

The measurement website

99, rue Beranger
92320 Chatillon - France

Tel : +33 (0)1 71 16 17 00

Fax : +33 (0)1 71 16 17 03

www.testoon.com